



GLOBAL GREEN CORPORATION

UL844 C1D2 LED Flood Light

Explosion Proof LED Flood Light Hazardous Location



Phillips 3030

40 Watt

80 CRI

50000hrs



FEATURES

- Phillips Chips
- Type B Ballast By Pass 100-277AC
- Replaces 250W MH
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 4000K, 5000K, 6000K
- Meanwell Driver
- Up to 80% energy savings
- Ultra-high performance LED delivers 140 lpw
- Suitable for dry or damp locations
- Motion Sensor
- Microwave Sensor
- Dali and Zigbee Integration



DIMENSIONS



APPLICATIONS

- Industrial Parks
- Mining
- Warehouses
- Petroleum Refineries
- Power Plants
- Heavy Industrial

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
40W	AC120-277V	4400 lm	180 degrees /4000K/5000k/6000K		>80
Efficiency	PF	Style	Install	Rated Life	Approvals
110lm/W	>0.95	Flood	Wall Mount	50000hrs	UL/cUL,DLC V4.0

ORDERING GUIDE

Example: GG-EXP-FLD-40W-840

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	Explosion- EXP Flood: FLD	40W	840	-CRI80, 4000K	
			850	-CRI80, 5000K	
			860	-CRI80, 6000K	



GLOBAL GREEN CORPORATION



Phillips 3030

100 Watt

80 CRI

50000hrs



5 YEAR
WARRANTY

UL844 C1D2 LED Flood Light

Explosion Proof LED Flood Light Hazardous Location

FEATURES

- Phillips Chips
- Type B Ballast By Pass 100-277AC
- Replaces 250W MH
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 4000K, 5000K, 6000K
- Meanwell Driver
- Up to 80% energy savings
- Ultra-high performance LED delivers 140 lpw
- Suitable for dry or damp locations
- Motion Sensor
- Microwave Sensor
- Dali and Zigbee Integration

DIMENSIONS



APPLICATIONS

- Industrial Parks
- Mining
- Warehouses
- Petroleum Refineries
- Power Plants
- Heavy Industrial

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
100W	AC120-277V	11000 lm	180 degrees /4000K/5000k/6000K		>80
Efficiency	PF	Style	Install	Rated Life	Approvals
110lm/W	>0.95	Flood	Wall Mount	50000hrs	UL/cUL,DLC V4.0

ORDERING GUIDE

Example: GG-EXP-FLD-100W-840

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	Explosion- EXP	Flood: FLD	100W	840 -CRI80, 4000K	
				850 -CRI80, 5000K	
				860 -CRI80, 6000K	



GLOBAL GREEN CORPORATION

UL844 C1D2 LED Flood Light

Explosion Proof LED Flood Light Hazardous Location



Phillips 3030

180 Watt

80 CRI

50000hrs



FEATURES

- Phillips Chips
- Type B Ballast By Pass 100-277AC
- Replaces 250W MH
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 4000K, 5000K, 6000K
- Meanwell Driver
- Up to 80% energy savings
- Ultra-high performance LED delivers 140 lpw
- Suitable for dry or damp locations
- Motion Sensor
- Microwave Sensor
- Dali and Zigbee Integration



DIMENSIONS



APPLICATIONS

- Industrial Parks
- Mining
- Warehouses
- Petroleum Refineries
- Power Plants
- Heavy Industrial

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
180W	AC120-277V	19800 lm	180 degrees /4000K/5000k/6000K		>80
Efficiency	PF	Style	Install	Rated Life	Approvals
110lm/W	>0.95	Flood	Wall Mount	50000hrs	UL/cUL,DLC V4.0

ORDERING GUIDE

Example: GG-EXP-FLD-180W-840

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	Explosion- EXP	Flood: FLD	180W	840 -CRI80, 4000K	
				850 -CRI80, 5000K	
				860 -CRI80, 6000K	