



GLOBAL GREEN CORPORATION

G24-G23 LED Type A - B

Ballast Compatible/Ballast Bypass: work with or without ballasts.



G24-G23

6 Watt

82 CRI

50000hrs



FEATURES

- Type A Plug and Play Electronic Ballast
- Type B Ballast By Pass 100-277AC or Magnetic Ballast Compatible
- Replaces CFL 13 Watt and CFL 26 Watt
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 2700K, 3000K, 3500K or 4000K
- Frosted lens for uniform diffuse appearance
- Up to 80% energy savings
- Ultra-high performance LED delivers 100 lpw
- Suitable for dry or damp locations
- Q- Quad Pin
- D- Dual Pin

DIMENSIONS



APPLICATIONS

- Schools
- Offices
- Warehouses
- Hospitals
- Subways
- Stores
- Underground parking lots

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
6W	AC120-277V	600 lm	120 degrees	2700K/3000K/3500k/4000K	>82
Efficiency	PF	Base	Shape	Rated Life	Approvals
100lm/W	>0.95	G24Q-G24D	G24	50000hrs	UL/cUL,

ORDERING GUIDE

Example: GG-G24-B-6W-840-HZ

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	G24-G23 AB: UL Type A-B-		6W	830 - CRI80, 3000K 835 - CRI80, 3500K 840 - CRI80, 4000K	HZ- Horizontal



GLOBAL GREEN CORPORATION

G24-G23 LED Type A - B

Ballast Compatible/Ballast Bypass: work with or without ballasts.



G24-G23

9 Watt

82 CRI

50000hrs



FEATURES

- Type A Plug and Play Electronic Ballast
- Type B Ballast By Pass 100-277AC or Magnetic Ballast Compatible
- Replaces CFL 13 Watt and CFL 26 Watt
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 2700K, 3000K, 3500K or 4000K
- Frosted lens for uniform diffuse appearance
- Up to 80% energy savings
- Ultra-high performance LED delivers 115 lpw
- Suitable for dry or damp locations
- Q- Quad Pin
- D- Dual Pin



DIMENSIONS



APPLICATIONS

- Schools
- Offices
- Warehouses
- Hospitals
- Subways
- Stores
- Underground parking lots

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
9W	AC120-277V	1020 lm	120 degrees	2700K/3000K/3500k/4000K	>82
Efficiency	PF	Base	Shape	Rated Life	Approvals
115lm/W	>0.95	G24Q-G24D	G24	50000hrs	UL/cUL, DLC V4.1

ORDERING GUIDE

Example: GG-G24-B-9W-840-HZ

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	G24-G23	AB: UL TypeA-B-	9W	830 - CRI80, 3000K 835 - CRI80, 3500K 840 - CRI80, 4000K	HZ- Horizontal

G24-G23 Vertical

Ballast Compatible/Ballast Bypass: work with or without ballasts.



G24-G23

6 Watt

82 CRI

50000hrs



FEATURES

- Type A Plug and Play Electronic Ballast
- Type B Ballast By Pass 100-277AC or Magnetic Ballast Compatible
- Replaces CFL 13 Watt and CFL 26 Watt
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 2700K, 3000K, 3500K or 4000K
- Frosted lens for uniform distribution of Light
- Up to 80% energy savings
- Ultra-high performance LED delivers 100 lpw
- Suitable for dry or damp locations
- Q-Quad Pin
- D- Dual Pin

DIMENSIONS



APPLICATIONS

- Schools
- Offices
- Warehouses
- Hospitals
- Subways
- Stores
- Underground parking lots

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
6W	AC120-277V	600 lm	120 degrees	2700K/3000K/3500k/4000K	>82
Efficiency	PF	Base	Shape	Rated Life	Approvals
100lm/W	>0.95	G24Q-G24D	G24	50000hrs	UL/cUL,

ORDERING GUIDE

Example: GG-G24-B-6W-840-V

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	G24-G23 AB: UL Type A-B-		6W	830 - CRI80, 3000K 835 - CRI80, 3500K 840 - CRI80, 4000K	V- Verticla



GLOBAL GREEN CORPORATION

G24-G23 Vertical

Ballast Compatible/Ballast Bypass: work with or without ballasts.

FEATURES

- Type A Plug and Play Electronic Ballast
- Type B Ballast By Pass 100-277AC or Magnetic Ballast Compatible
- Replaces CFL 13 Watt and CFL 26 Watt
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 2700K, 3000K, 3500K or 4000K
- Frosted lens for uniform distribution of Light
- Up to 80% energy savings
- Ultra-high performance LED delivers 115 lpw
- Suitable for dry or damp locations
- Q-Quad Pin
- D- Dual Pin



G24-G23

9 Watt

82 CRI

50000hrs



DIMENSIONS



APPLICATIONS

- Schools
- Offices
- Warehouses
- Hospitals
- Subways
- Stores
- Underground parking lots

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
9W	AC120-277V	1020 lm	120 degrees	2700K/3000K/3500k/4000K	>82
Efficiency	PF	Base	Shape	Rated Life	Approvals
100lm/W	>0.95	G24Q-G24D	G24	50000hrs	UL/cUL, DLC V4.1

ORDERING GUIDE

Example: GG-G24-B-9W-840-V

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	G24-G23	AB: UL TypeA-B-	9W	830 - CRI80, 3000K 835 - CRI80, 3500K 840 - CRI80, 4000K	V- Verticla