



GLOBAL GREEN CORPORATION

LED Linear High Bay Light

Suspension Mounted LED Highbay.

FEATURES

- Phillips Chips
- Type B Ballast By Pass 100-277AC
- Replaces 250W MH
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 4000K, 5000K, 6000K
- Meanwell Driver
- Up to 80% energy savings
- Ultra-high performance LED delivers 130 lpw
- Suitable for dry or damp locations
- Motion Sensor
- Microwave Sensor
- Dali and Zigbee Intergration

Phillips 3030


40 Watt

80 CRI

50000hrs



DIMENSIONS



APPLICATIONS

- Industrial Parks
- Strip Malls
- Warehouses
- Parking Garages
- Subways
- Underground parking lots

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
40W	AC120-277V	5200 lm	180 degrees /4000K/5000k/6000K		>80
Efficiency	PF	Style	Install	Rated Life	Approvals
130lm/W	>0.95	Linear	Suspension	50000hrs	UL/cUL, DLC V4.0

ORDERING GUIDE

Example: GG-LN-HB-40W-840

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	Linear Highbay- LN	High Bay: HB	40W	840 -CRI80, 4000K	
				850 -CRI80, 5000K	
				860 -CRI80, 6000K	



GLOBAL GREEN CORPORATION

LED Linear High Bay Light

Suspension Mounted LED Highbay.

FEATURES

- Phillips Chips
- Type B Ballast By Pass 100-277AC
- Replaces 250W MH
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 4000K, 5000K, 6000K
- Meanwell Driver
- Up to 80% energy savings
- Ultra-high performance LED delivers 130 lpw
- Suitable for dry or damp locations
- Motion Sensor
- Microwave Sensor
- Dali and Zigbee Intergration



Phillips 3030

60 Watt


80 CRI

50000hrs



DIMENSIONS

APPLICATIONS



- Industrial Parks
- Strip Malls
- Warehouses
- Parking Garages
- Subways
- Underground parking lots

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
60W	AC120-277V	7800 lm	180 degrees /4000K/5000k/6000K		>80
Efficiency	PF	Style	Install	Rated Life	Approvals
130lm/W	>0.95	Linear	Suspension	50000hrs	UL/cUL, DLC V4.0

ORDERING GUIDE

Example: GG-LN-HB-60W-840

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	Linear Highbay- LN	High Bay: HB	60W	840	-CRI80, 4000K
				850	-CRI80, 5000K
				860	-CRI80, 6000K



GLOBAL GREEN CORPORATION

LED Linear High Bay Light

Suspension Mounted LED Highbay.

FEATURES

- Phillips Chips
- Type B Ballast By Pass 100-277AC
- Replaces 400W MH
- Environmentally friendly; no mercury or lead
- 5 year product warranty
- Choice of 4000K, 5000K, 6000K
- Meanwell Driver
- Up to 80% energy savings
- Ultra-high performance LED delivers 130 lpw
- Suitable for dry or damp locations
- Motion Sensor
- Microwave Sensor
- Dali and Zigbee Intergration

Phillips 3030

90 Watt


80 CRI

50000hrs



DIMENSIONS

APPLICATIONS



- Industrial Parks
- Strip Malls
- Warehouses
- Parking Garages
- Subways
- Underground parking lots

SPECIFICATIONS

Watts	Volts	Lumens	Beam Angle	CCT	CRI
90W	AC120-277V	11700 lm	180 degrees /4000K/5000k/6000K		>80
Efficiency	PF	Style	Install	Rated Life	Approvals
130lm/W	>0.95	Linear	Suspension	50000hrs	UL/cUL, DLC V4.0

ORDERING GUIDE

Example: GG-LN-HB-90W-840

Company	Series	Type	Watts	CCT	Mode
GG - Global Green	Linear Highbay- LN	High Bay: HB	90W	840 -CRI80, 4000K	
				850 -CRI80, 5000K	
				860 -CRI80, 6000K	